



SUMMIT INTERNATIONAL FLOORING STRENGTH SERIES RUBBER FLOORING CLEANING AND MAINTENANCE GUIDE

Note: Sealing the floor is not a necessary step and in fact, it is discouraged in very abusive applications (e.g., Health club free weight area or ice hockey perimeter flooring). However, high color percentage floors (>50%) or areas that experience foot traffic will greatly benefit by being sealed.

A. Maintenance For Un-sealed Floors.

1. Strength Series Rubber Flooring can be cleaned much like carpeting.
2. Daily vacuuming is encouraged to keep dust to a minimum.
3. If the flooring cannot be fully cleaned with a vacuum, damp mopping with a mild soap and water solution will usually be sufficient.
 - a) It is important not to get the flooring too wet as this may have an adverse affect on the adhesive system employed.
 - b) Change the soap and water solution often!
4. Use a wet vacuum to remove excess water from the flooring.
5. Be sure to use a clean mop. This will keep your floor smelling fresh and clean.

B. Post Construction Maintenance For Sealed Floors.

1. Sweep the floor clean.
2. Dry vacuum to ensure any fine soil is removed.
3. Wet scrub floor with TASKI Profi cleaner (6-8 oz / gl of water) using buffer or autoscrubber with a TASKI contact pad or soft nylon brush.
 - a) TASKI floor care products are manufactured by JohnsonDiversey™ and can be found at many janitorial supply houses.
 - b) JohnsonDiversey™ customer service hotline is 800-626-5015
 - c) Look under institutional floor care products on their website at <http://www.diverseylever.com>
4. Recover soiled solution, rinse, and allow to dry thoroughly (6-8 hours).

C. Initial Treatment

Apply 3 thin coats of TASKI Vision Matte. Allow proper drying time before applying next coat. Note: Apply floor finish with synthetic wax mop. While the finish is wet, buff the floor with floor buffer (150-300 rpm) and soft nylon brush. This application drives the finish into the floor and prompts proper sealing and coating of the floor.