Summit International Flooring

# TRIATHLON 700 SERIES

**All Purpose Rubber Flooring**

Available in 4' Roll Widths & 3' width
available upon request w/10% upcharge

PRODUCT SPECIFICATIONS

| Technical Data | Standard/Norms | Data |
|---|---|---|
| Compostion | | SBR with high EPDM content, up to 100% |
| Style | | Roll goods - square edges only |
| Overall Thickness | | 1/8" (4mm) 1/4" (6mm), 5/6" (8mm), 3/8" (10mm), 1/2" (12mm) nominal |
| Size | | 4' standard, 3' available |
| Shore Hardness | ASTM D2240 | 60 Indentation Hardness |
| Density | ASTM D792 | 60.0 lbs/cubic foot |
| Rebound | ASTM D3574 (5/16") | 45 - 60% |
| Tensile | ASTM D412 | 150 PSI |
| Taber Abrasion | ASTM C501 | 0.45 grams - weight loss |
| Static Load | ASTM F970 | 0.004 inches residual compression |
| Static Coefficient of Friction | ASTM ASTM C1028 | Dry: .98; Wet: .83 |
| Smoke Density | ASTM E84 | Pass |
| Compression Set | ASTM D395B | 88% recovered |
| Material Emmssions - VOC | ASTM D5116 | Pass |
| Granular Color | 1-3 SBR EPDM - Black 8/16 SBR | |
| Storage | Rolls on end, minimum 55 degrees Fahrenheit. Less than 50% humidity | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |