



Summit International Flooring

TRIATHLON 800 Series Rubber Flooring Cleaning & Maintenance

Sealant Application and Maintenance Guidelines

A) Post construction

- Sweep the floor. Dry vacuum to ensure any fine soil is removed.
- Wet scrub floor with Taski Profi cleaner (6 - 8 oz/gal of water) using buffer or auto scrubber with Taski contact pad or soft nylon brush.
- Wet vacuum soiled solution, rinse, and allow to dry thoroughly (6 – 8 hours).

B) Initial application of sealer

Apply 3 thin coats of Vision Matte.

- Allow proper drying time before applying next coat.
Note: Apply floor finish with synthetic wax mop. While the finish is wet, buff the floor with floor buffer (150 – 300 rpm) and soft nylon brush. This application drives the finish into the floor and prompts proper sealing and coating of the floor.

C) Daily cleaning or as needed (sealed floor)

- Dry vacuum floor thoroughly.
- Auto scrub or wet mop floor using TASKI Wiwax.

Note: In an office environment, the floor may become scuffed due to heavy foot traffic and may require more frequent spray or dry buffing with a mint or white pad. When spray buffing use TASKI Wiwax diluted 50/50 with water.

D) Periodic cleaning as needed (sealed floor)

- Dry vacuum floor thoroughly.
- Wet scrub floor with TASKI Profi (4 oz/gal). This application is done with an auto scrubber or buffer and wet vacuums. Use TASKI purple pad for scrubbing the floor.
- Allow solution to remain on the floor for 5 minutes.
- Wet vacuum soiled solution. Rinse and allow to dry (1 – 2 hours).
- Apply 1 – 2 thin coats of TASKI Vision Matte using wet buffing with soft nylon brush.

E) A few tips about sealers when working with rubber floors

- Use high suction CFM (cubic feet per meter) vacuum to pick up dust.
- Wait for floor to dry between applications of floor finish or sealer.
- Apply floor finish (thin coats) with wax mop and follow floor buffer with a soft nylon brush.
- For large areas, use an auto-scrubber with a contact pad or soft nylon brush to clean the floor daily.
- For food areas: cleaning should be done with Profi (2 – 4 oz/gal).
- Removing gum: use a generic gum remover.
- For areas with high traffic, floors may be top scrubbed and recoated as needed.