



# Grassland

<b>PRODUCTSPECIFICATIE</b> ANWENDUNG/APPLICATION/TOEPASSING/APLICACIÓN/INDICAZIONE USO	LANDSCAPE, GARDEN LAWNS, ROOFGARDENS, INFRASTRUCTURE			
<b>PRODUCTPROCES</b> HERSTELLUNGSVERFAHREN/MODE DE FABRICATION/PRODUCTION PROCESS/ PROCESO DE FABRICACIÓN/TIPO DI PRODUZIONE	TUFTED			
<b>PRODUCENT</b> HERSTELLER/PRODUCTEUR/PRODUCER/PRODUCTOR/PRODUTTORE	GRASSPARTNERS B.V. GENEMUIDEN, THE NETHERLANDS			
<b>POOLMATERIAAL</b> POLMATERIAL/COMPOSITION DU VELOURS/PILE MATERIAL/ COMPOSICIÓN DE LA PILA/ COMPOSIZIONE FILATO	100% BGY PE MONOFILAMENTS STRAIGHT+TEXTURIZED. ENVIRONMENT FRIENDLY, U.V. STABILIZED, 14.400 DTEX (7.200 PE / 7200 PE)			
<b>KLEUR</b> FARBE/COULEUR/COLOR/COLOR/COLORE	Emerald Apple /Summer Nut			
<b>UV-STABILITEIT</b> UV-STABILITÄT/UV STABILITÉ UV/UV STABILITEIT/ESTABILIDAD UV/STABILITA UV	DIN 53387 STANDARD (6000 HRS) W.O.M TEST			
<b>TUFTDOEK</b> TRÄGER/DOSSIER PRIMAIRE/PRIMARY BACKING/BACKING PRINCIPAL/SUPPORTO PRIMARIO	100% PP -TAPES WOVEN + 10% PP COLOURED FLEECE CA. 135 GR/M <sup>2</sup>			
<b>BACKING</b> RÜCKEN/DOSSIER SECONDAIRE/SECUDAIRY BACKING/BACKING SECUNDARIO/ SPALMATURA ROVESCIO	(SBR) LATEX COMPOUND ± 1000 GR/M <sup>2</sup>			
<b>WATERDOORLATENDHEID</b> WASSERDURCHLASSIGKEIT/PERMÉABILITÉ/WATER PERMEABILITY/ PERMEABILIDAD AL ACQUA	± 60 L / MIN / M <sup>2</sup>			
	Grassland 25	Grasland 30	Grassland 40	GrassLand Plus
<b>POOLHOOGTE</b> POLHÖHE/HAUTEUR DU VELOURS/PILE HEIGHT/ALTURA DE LA PILA /ALTEZZA FILO	25 MM (±10%)	30 MM (±10%)	40 MM (±10%)	30 MM (±10%)
<b>TOTALE HOOGTE</b> GESAMTHÖHE/HAUTEUR TOTALE /TOTAL HEIGHT/ALTURA TOTAL /ALTEZZA COMPLESSIVA	27 MM (±10%)	32 MM (±10%)	42 MM (±10%)	32 MM (±10%)
<b>POOLGEWICHT</b> POLEINSATZGEWICHT/POIDS DU VELOURS/PILEWEIGHT/PESO DE LA PILA/PESO FILATO	1334 GR/M <sup>2</sup> (±10%)	1967 GR/M <sup>2</sup> (±10%)	2300 GR/M <sup>2</sup> (±10%)	2967 GR/M <sup>2</sup> (±10%)
<b>TOTAAL GEWICHT</b> GESAMTGEWICHT/POIDS TOTAL/TOTAL WEIGHT/PESO TOTAL/PESO MANTO	2219 GR/M <sup>2</sup> (±10%)	2852 GR/M <sup>2</sup> (±10%)	3185 GR/M <sup>2</sup> (±10%)	3852 GR/M <sup>2</sup> (±10%)
<b>TUFTDELING</b> TUFTEILUNG/JAUGE / GAUGE/GALGA/PASSO	*3/8*	*3/8*	*3/8*	*3/8*
<b>STEKENAANTAL (10 CM<sup>1</sup>)</b> STICHZAHL /NOMBRE DE POINTS/STITCHES/DENSIDAD PUNTOS /PUNTI LINEARI	± 14	± 18	± 16	± 28
<b>STEKENAANTAL (M<sup>2</sup>)</b> STICHZAHL/NOMBRE DE POINTS/STITCHES/DENSIDAD PUNTOS/PUNTI LINEARI	± 14.700	± 18.900	± 16.800	± 29.600
<b>INFILL SILICASAND 0,5-1.0 MM,80% Ø</b> VERFÜLLUNG/REPLISSAGE/INFILL/RELLENO/INTASO	± 5-10 KG/M <sup>2</sup>	± 5-10 KG/M <sup>2</sup>	± 5-10 KG/M <sup>2</sup>	± 5-10 KG/M <sup>2</sup>
<b>ROL AFMETING</b> ROLLEN DIMENSION/ DIMENSION DE ROULEAU/ROLL DIMENSION/DIMENSIÓN DE ROLLO/ DIMENSIONE DEL ROTOLO	±25 Lm1	±25 Lm1	±25 Lm1	±25 Lm1

**GRASS**  **PARTNERS**

Puttenstraat 7, 8981 BP Genemuiden, The Netherlands / info@grasspartners.com / www.grasspartners.com  
BTWnr NL 8583.71.182.B01 / K.v.K 705550786 / IBAN NL673 RABO 0326 8479 87 / BIC RABONL2U