

# ARKIT

french design floor

## ARKIT is a heterogeneous polyvinyl chloride floor coverings (LVT category)

<b>Tile dimension (cm)</b>	EN 427	91,4 x 91,4 cm
<b>Packaging</b>		6 tiles/box 5sqm
<b>Overall thickness</b>	EN 428	2,5 mm
<b>Wear layer thickness</b>	EN 429	0,7 mm
<b>Weight</b>	EN 430	4,450 kg/sqm
<b>Use classification</b>	EN 685	Class 34 / 43 = Heavy commercial
<b>Wear group</b>	EN 649	Group T = < 2 mm <sup>3</sup>
<b>Reaction to fire</b>	EN 13501-1	B <sub>fl</sub> -s1 = Professional/Private use
<b>Slip resistance</b>	EN 13893	0,40 ( DS ) = DS: 0,4
<b>Residual indentation after static load</b>	NF EN ISO 24343-1	0,05 mm
<b>Dimensional stability</b>	NF EN ISO 23999	0,02 %
<b>Dimensional curling</b>	NF EN ISO 23999	1,3 mm
<b>Castor chair</b>	ISO 4918	Yes (type W)
<b>Thermal conductivity</b>	EN 12664	0,0132 sqm K/W
<b>Resistance to staining</b>	EN 423	Class 0 and 1
<b>Emissions TVOC</b>	EN ISO 16000	< 20 µg/m <sup>3</sup>
<b>Color fastness to light</b>	ISO 105-B02	≥ 6



Information on the level of emission of volatile substances in indoor air, presenting a risk of inhalation toxicity on a scale of class from A+ (very slow emissions) to C (high emissions).



EN 14041 : 2004



For more information please contact our Technical Service: 03.85.20.54.18  
or [contact@arkit-floors.com](mailto:contact@arkit-floors.com)



[www.arkit-floors.com](http://www.arkit-floors.com)